

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 21.11.2023

Version number 1

Revision: 21.11.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: MR® 79 Remover AMS 2644 - Class 2- Solvent (Aerosol)**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Life cycle stages**
  - F Formulation or re-packing
  - IS Use at industrial Sites
- **Sector of Use**
  - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category**
  - PC14 Metal surface treatment products
  - PC9a Coatings and paints, thinners, paint removers
  - PC35 Washing and cleaning products (including solvent based products)
- **Process category**
  - PROC7 Industrial spraying
  - PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
  - PROC13 Treatment of articles by dipping and pouring
- **Environmental release category**
  - ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
- **Article category AC7 Metal articles**
- **Application of the substance / the mixture**
  - Testing material for nondestructive surface crack detection
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
  - MR Chemie GmbH
  - Nordstr. 61-63
  - 59427 Unna (Germany)
  - Tel. +49 (0)2303 95151 0
  - Fax: +49 (0)2303 95151 10
  - post@mr-chemie.de
  - www.mr-chemie.de
- **Further information obtainable from:**
  - MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38, QS@mr-chemie.de
- **1.4 Emergency telephone number:**
  - 24h- Emergency Contact Phone Number For Chemical Emergency, Spill, Leak, Fire, Exposure or Accident (WISAG FMO Cargo Service GmbH & CO.KG)
  - Call Day or Night within USA and Canada: 1 800 424 9300
  - Outside USA and Canada: 001 703 527 3887
  - In-Country Emergency Number for:
 

Germany:	0800-181-7059	
China:	4001 204937	(Mandarin)
Hong Kong:	800 968 793	(Cantonese)
India:	000 800 100 7141	(Hindi)
South Africa:	0 800 983 611	(English)

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
  - The mixture is classified according to Regulation (EC) No 1272/2008 according to the most recent ATP.
  - Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
  - Eye Irrit. 2 H319 Causes serious eye irritation.
  - STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 21.11.2023

Version number 1

Revision: 21.11.2023

**Trade name: MR® 79 Remover AMS 2644 - Class 2- Solvent (Aerosol)**

(Contd. of page 1)

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**  
acetone
- **Hazard statements**  
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.
- **Precautionary statements**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P405 Store locked up.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**  
EUH066 Repeated exposure may cause skin dryness or cracking.  
Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.  
Buildup of explosive mixtures possible without sufficient ventilation.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-XXXX	acetone ----- Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	50 - 60%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-XXXX	butane (containing < 0,01 % butadiene (203-450-8)) ----- Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10 - 20%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-XXXX	propane ----- Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10 - 20%

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 21.11.2023

Version number 1

Revision: 21.11.2023

**Trade name: MR® 79 Remover AMS 2644 - Class 2- Solvent (Aerosol)**

CAS: 67-63-0	2-Propanol	(Contd. of page 2)
EINECS: 200-661-7	Flam. Liq. 2, H225	≥ 5 - < 10%
Reg.nr.: 01-2119457558-25-XXXX	Eye Irrit. 2, H319; STOT SE 3, H336	

· **Propellant:** Propane-Butane

· **Additional information:**

Wording of the listed hazard phrases are indicated in section 16 and relate to individual raw components.

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Take affected persons out into the fresh air.  
Immediately remove any clothing soiled by the product.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

If skin irritation continues, consult a doctor.  
Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Not relevant - aerosol can.

· **Information for doctor:**

Grease with skin-cream to restore fat film in order to prevent skin inflammation.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)

· **5.3 Advice for firefighters**

· **Protective equipment:** Wear self-contained respiratory protective device.

### SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 21.11.2023

Version number 1

Revision: 21.11.2023

**Trade name: MR® 79 Remover AMS 2644 - Class 2- Solvent (Aerosol)**

(Contd. of page 3)

See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, e.g. electric lights. Do not pierce or burn, even after use.  
Protect against electrostatic charges.  
Use explosion-proof apparatus / fittings and spark-proof tools.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **Recommended storage temperature:** 5 - 45°C, 41 - 113 °F
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see section 7.

#### · Ingredients with limit values that require monitoring at the workplace:

##### 67-64-1 acetone

IOELV (EU)	Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
WEL (Great Britain)	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
AGW (Germany)	Long-term value: 1200 mg/m <sup>3</sup> , 500 ppm 2(I);DFG, EU

##### 74-98-6 propane

AGW (Germany)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm 4(II);DFG
---------------	---

##### 106-97-8 butane (containing < 0,01 % butadiene (203-450-8))

WEL (Great Britain)	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
AGW (Germany)	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm 4(II);DFG

##### 67-63-0 2-Propanol

WEL (Great Britain)	Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm Long-term value: 999 mg/m <sup>3</sup> , 400 ppm
AGW (Germany)	Long-term value: 500 mg/m <sup>3</sup> , 200 ppm 2(II);DFG, Y

#### · DNELs

##### 67-64-1 acetone

Dermal	Long-term - systemic effects, worker	186 mg/kg bw/day (worker)
Inhalative	Long-term - systemic effects, worker	1,210 mg/m <sup>3</sup> (worker)

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.11.2023

Version number 1

Revision: 21.11.2023

**Trade name: MR® 79 Remover AMS 2644 - Class 2- Solvent (Aerosol)**

(Contd. of page 4)

	Long-term - local effects, worker	2,420 mg/m <sup>3</sup> (worker)
<b>67-63-0 2-Propanol</b>		
Dermal	Long-term - systemic effects, worker	888 mg/kg bw/day (worker)
Inhalative	Long-term - systemic effects, worker	500 mg/m <sup>3</sup> (worker)

**· DNEL (Derived No Effect Level) for the general population**

<b>67-64-1 acetone</b>		
Oral	Long term - systemic effects, general population	62 mg/kg bw/day (general population)
Dermal	Long term - systemic effects, general population	62 mg/kg bw/day (general population)
Inhalative	Long term - local effects, general population	200 mg/m <sup>3</sup> (general population)
<b>67-63-0 2-Propanol</b>		
Oral	Long term - systemic effects, general population	26 mg/kg bw/day (general population)
Dermal	Long term - systemic effects, general population	319 mg/kg bw/day (general population)
Inhalative	Long term - systemic effects, general population	89 mg/m <sup>3</sup> (general population)

**· PNECs**

<b>67-64-1 acetone</b>		
Aquatic compartment - freshwater		10.6 mg/L (freshwater)
Aquatic compartment - marine water		1.06 mg/L (marine water)
Aquatic compartment - sediment freshwater		30.4 mg/kg sed dw (sediment fresh water)
Aquatic compartment - sediment marine water		3.04 mg/kg sed dw (sediment marine water)
Terrestrial compartment - soil		29.5 mg/kg dw (soil)
<b>67-63-0 2-Propanol</b>		
Aquatic compartment - freshwater		140.9 mg/L (freshwater)
Aquatic compartment - marine water		140.9 mg/L (marine water)
Aquatic compartment - sediment freshwater		552 mg/kg sed dw (sediment fresh water)
Aquatic compartment - sediment marine water		552 mg/kg sed dw (sediment marine water)
Terrestrial compartment - soil		28 mg/kg dw (soil)
Sewage treatment plant		2,251 mg/L (sewage treatment plant)
Oral secondary poisoning		160 mg/kg food (secondary poisoning (food))

**· Ingredients with biological limit values:**

<b>67-64-1 acetone</b>		
BGW (Germany)	80 mg/l	Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton
<b>67-63-0 2-Propanol</b>		
BGW (Germany)	25 mg/l	Untersuchungsmaterial: Vollblut Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton
	25 mg/l	Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 21.11.2023

Version number 1

Revision: 21.11.2023

**Trade name: MR® 79 Remover AMS 2644 - Class 2- Solvent (Aerosol)**

(Contd. of page 5)

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**  
Filter AX  
For good ventilation provide, this can be achieved by local or space exhaust. If the concentration lies over the job limit values, then, a certified respirator suitable for this purpose must be used.
- **Protection of hands:**



Protective gloves

Check the permeability prior to each renewed use of the glove.  
For the protection against chemicals in areas with heightened risk of injury (mechanical hazard) no recommendation for a suitable glove material can be given.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
Butyl rubber, BR  
Recommended thickness of the material:  $\geq 0.5$  mm  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
Value for the permeation: Level  $\leq 6$   
Supplier for suitable protection gloves:  
ASD ArbeitsSicherheit Dortmund  
Torstr. 101 - 37355 Niederorschel OT Rüdigershagen  
Tel.: 02301 / 919543 - Fax: 02301 / 9453893  
E-Mail: m.schnellhardt@t-online.de - <http://www.arbeitssicherheitdortmund.de>  
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

<b>Form:</b>	Aerosol
<b>Colour:</b>	Colourless
<b>Odour:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.

(Contd. on page 7)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.11.2023

Version number 1

Revision: 21.11.2023

**Trade name: MR® 79 Remover AMS 2644 - Class 2- Solvent (Aerosol)**

(Contd. of page 6)

· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	Not applicable, as aerosol.
· <b>Flash point:</b>	-80 °C Basis: propellant
· <b>Flammability (solid, gas):</b>	Not applicable.
· <b>Auto-ignition temperature:</b>	Not determined - aerosol.
· <b>Decomposition temperature:</b>	Not determined.
· <b>Ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible. Not determined.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1.5 Vol %
<b>Upper:</b>	13 Vol %
· <b>Vapour pressure at 20 °C:</b>	8,300 hPa Basis: propellant
· <b>Density at 20 °C:</b>	0.793 g/cm <sup>3</sup> Basis: active substance
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent separation test:</b>	
<b>Organic solvents:</b>	100.0 %
<b>VOC (EU)</b>	100.00 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
Danger of bursting of the aerosol can during overheating
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 21.11.2023

Version number 1

Revision: 21.11.2023

**Trade name: MR® 79 Remover AMS 2644 - Class 2- Solvent (Aerosol)**

(Contd. of page 7)

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

#### 67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rbt)

#### 106-97-8 butane (containing < 0,01 % butadiene (203-450-8))

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

#### 67-63-0 2-Propanol

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rbt)
Inhalative	LC50/4 h	30 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **General remarks:**
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system.  
Water hazard class 1: weakly water-endangering
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Eliminate the pure, unchanged substance in accordance with local regulations.  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.11.2023

Version number 1



Revision: 21.11.2023

**Trade name: MR® 79 Remover AMS 2644 - Class 2- Solvent (Aerosol)**

(Contd. of page 8)

- **Waste disposal key:**  
For this product no waste key number can be specified, because only the intended purpose permits an allocation. The waste key number is to be specified in arrangement with the regional waste disposal.  
The indications for Waste key reflect the pure unmodified product and are only a recommendation.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

<ul style="list-style-type: none"> <li>· <b>14.1 UN-Number</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	UN1950
<ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG</b></li> <li>· <b>IATA</b></li> </ul>	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
<ul style="list-style-type: none"> <li>· <b>14.3 Transport hazard class(es)</b></li> <li>· <b>ADR</b></li> </ul>	<div style="text-align: center;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>
<ul style="list-style-type: none"> <li>· <b>IMDG, IATA</b></li> </ul>	<div style="text-align: center;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>
<ul style="list-style-type: none"> <li>· <b>14.4 Packing group</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>14.5 Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>	No
<ul style="list-style-type: none"> <li>· <b>14.6 Special precautions for user</b></li> <li>· <b>Hazard identification number (Kemler code):</b> -</li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Code</b></li> </ul>	Warning: Gases. F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of
<ul style="list-style-type: none"> <li>· <b>Segregation Code</b></li> </ul>	Segregation as for the appropriate subdivision of

(Contd. on page 10)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.11.2023

Version number 1

Revision: 21.11.2023

**Trade name: MR® 79 Remover AMS 2644 - Class 2- Solvent (Aerosol)**

(Contd. of page 9)

·	class 2.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN1950, AEROSOLS, 2.1

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Waterhazard class:** Water hazard class 1: slightly hazardous for water.
- **VOC (EU)** 793.0 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

- **Relevant phrases**  
The wording of the listed risk phrases are those of the individual raw materials.  
H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.
- **Recommended restriction of use**  
Existing national and local laws concerning chemicals are to be considered.
- **Department issuing SDS:**  
MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38
- **Contact:**  
MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38, QS@mr-chemie.de
- **Abbreviations and acronyms:**  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 11)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 21.11.2023

Version number 1

Revision: 21.11.2023

**Trade name: MR® 79 Remover AMS 2644 - Class 2- Solvent (Aerosol)**

(Contd. of page 10)

VOC: Volatile Organic Compounds (USA, EU)  
DNEL: Derived No-Effect Level (UK REACH)  
PNEC: Predicted No-Effect Concentration (UK REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Gas 1A: Flammable gases – Category 1A  
Aerosol 1: Aerosols – Category 1  
Press. Gas (Comp.): Gases under pressure – Compressed gas  
Flam. Liq. 2: Flammable liquids – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· \* **Data compared to the previous version altered.**

GB